


VDS6200 Video Transmission Set

Features

- Supports all type AHD (Analog HD) CCTV cameras, such as 720p and 1080p resolutions.
- Sends DC power (Safety methods) from Local side to Remote side, at the same time reverse send video use a single coaxial cable.
- More than 800 meters of transmission distance from Local Unit to Remote Unit.
- Thick or heavy duty coaxial cables increase the transmission distance to be more than 1,000 meters.



VDS6200 Connection Diagrams

Specification of VDS6200-RU Sender

Physical Specifications (6200-RU)	
Unit Dimensions	(L x W x H): 76mm x 50mm x 25mm
Weight	132 grams

Environmental Specifications (6200-RU)	
Operating Temperature	-10 to 45°C (14 to 113°F)
Relative Humidity	20% to 90%, non-condensing

Specification of VDS6200-LU Viewer

Physical Specifications (6200-LU)	
Unit Dimensions	(L x W x H): 84mm x 50mm x 25mm
Weight	120 grams

Environmental Specifications (6200-LU)	
Operating Temperature	-10 to 40°C (14 to 104°F)
Relative Humidity	20% to 90%, non-condensing

Biwave Technologies offers the Best CCTV Solutions over Coaxial Cable.

Contact

Biwave Technologies, Inc.
info@biwave.com

International Sales:
Phone: +886-2-2735-5511
Fax: +886-2-2736-5914

Engineering Facilities:
Phone: +886-3-377-0015
Fax: +886-3-367-3604